



## 350 PLUS

## 351 PLUS 352 PLUS

## 355 PLUS

NEW!



mm 1600

mm 400

mm 720



mm 650

mm 830

mm 1950

mm 700



mm 1950

mm 1150

### TECHNICAL FEATURES

- Versatile, handy and powerful, essential for all dust collections.
- Powerful and reliable induction motors.
- Suitable for direct connection to wood processing machines.
- Aluminum suction fan.
- Supplied as assembly kit.

### STANDARD FITTINGS

- Base with pivoting wheels.
- Flexible pipe 2 m long with ART. 350 PLUS
- Floor conveyor for ART 351/352
- Package with 5 dust filter-bags

### CARACTERÍSTICAS TÉCNICAS

- Robustos, versátiles y manejables, indispensables en todas las operaciones de aspiración del serrin virutas
- Motores de inducción potentes y fiables
- Adaptación para el acoplamiento con máquinas de carpintería
- Ventilador de aspiración de aluminio
- Se suministran en Kit de montaje

### EQUIPAMIENTO DE SERIE

- Base con ruedas giratorias.
- Tubo flexible longitud 2 m. con ART. 350 PLUS
- Boquilla para pavimentos para ART 351/352
- Bolsa filtrante para virutas
- Paquete de 5 bolsas de nylon para la recogida de polvo

### Technical data

### Datos técnicos

ART.	Code Código	WATT	M <sup>3</sup> /h	press. mm H <sub>2</sub> O	mm	a x b x h mm	Kg
350 PLUS	8.67.03.23	900 <sup>1</sup>	950	175	100x1	750x460x460	30
351 PLUS	8.67.04.22	1500 <sup>1</sup>	2700	300	100x2	920x580x580	47
352 PLUS	8.67.04.32	1500 <sup>3</sup>	2700	300	100x2	920x580x580	47
355 PLUS	8.67.07.32	2200 <sup>3</sup>	3900	305	100x3	1170x560x570	62

<sup>1</sup> 230 Volt - 50Hz single-phase motor - Motor monofásico 230 Volt - 50Hz  
<sup>3</sup> 400 Volt - 50Hz three-phase motor - Motor trifásico 400 Volt - 50Hz